SPECIFICATIONS

AND

CONTRACT DOCUMENTS

FOR

Index B

Aircraft Rescue Firefighting (ARFF) Vehicle

AT

CHARLOTTE COUNTY AIRPORT
PUNTA GORDA, FLORIDA

FAA AIP No. 3-12-0067-_____

FDOT FM No. _____

PREPARED BY

CHARLOTTE COUNTY AIRPORT AUTHORITY

December, 2013

FOR BIDDING

CHARLOTTE COUNTY AIRPORT AUTHORITY
INVITATION FOR BID
BID ITEM: INDEX B AIRCRAFT RESCUE FIREFIGHTING (ARFF) VEHICLE

December 30, 2013

Sealed Bids for a new ARFF Vehicle will be received at the Administrative Office of the Charlotte County Airport Authority, 28000 Airport Road A-1, Punta Gorda, Florida 33982, until 2 p.m., on 21 February 2014.

A, General Bidding Requirements

1. All bids must be made on the bid form furnished by the Charlotte County Airport Authority (Authority). No bid will be considered unless the bid form is properly signed.

2. Vendors must provide unit prices any time unit prices are requested in the units requested. These unit prices must be proper and balanced so as to allow fair adjustments in quantities as required by the Authority. All prices will remain firm for a period of Ninety (90) days from date of bid opening.

2a. Bid Bond: A bid bond or certified check in the amount of 5% of the enclosed bid is required.

2b. Performance Bond: Prior to commencement of the work the Vendor shall furnish a Performance Bond in the amount of the Bid. This Performance Bond shall guarantee the vendors obligations under this contract. Cost of this bond shall not be reimbursed to the vendor by the Authority.

3. Any transportation and/or any other charges incurred in delivering the product as specified must be included in the bid price. FOB destination shall apply unless exception is made in the specifications.

4. Any discounts or terms must be shown on the bid form. Such discounts, if any, will be considered and computed in the tabulation of the bids. In no instance should terms for less than 15 days payment be offered.

5. Bidders taking exception to any part or section of these specifications shall indicate such exceptions on a separate sheet entitled "EXCEPTIONS TO SPECIFICATIONS". Failure to indicate any exceptions shall be interpreted as the bidders intent to fully comply with the specifications as written.

6. The Authority reserves the right to formally amend and/or clarify the requirements of the bid specifications where it deems necessary. Any such addendum/clarification shall be in writing and shall be distributed to all parties who received the original bid specifications and are eligible for consideration prior to the deadline for submission of bids.

7. The Authority reserves the right to accept or reject any and all bids and to waive any informalities or irregularities, in the best interest of the Authority. The Authority is not liable for any costs incurred by the responding parties.

8. All bids shall be delivered to the Charlotte County Airport Authority
Administration Building
Corner of Viking Avenue and Piper Road
Punta Gorda, FL 33982
or mail to:
Charlotte County Airport Authority
28000 A-1 Airport Road
Punta Gorda, FL 33982
by 2 p.m. on 21 February 2014 as stated in the Legal Notice. Late bids may not be accepted.

9. Bids must be placed in a sealed envelope, and plainly marked as follows: (1) The date and time of receipt of the bids by the Authority's Administration Office. (2) The bid title for which the bidder is submitting the bid.

Special Note: All bids sent by courier service must have the bid title on the outside of the courier packet.

10. The Authority as a political subdivision of the State of Florida is exempt from the payment of Florida sales tax to its vendors under Chapter 212, Florida Statutes. All successful bidders will be provided a copy of Authority's Certificate of Exemption upon contract award.

Corporations, individuals and other entities are impacted by Chapter 212, Florida Statutes according to the type of service, sale of commodity or other contractual agreement to be made with Authority. By submittal of a properly executed response to a bid request from the Authority, the bidder is acknowledging that he is aware of his statutory responsibilities for sales tax under Chapter 212, Florida Statutes.

Authority is also exempt from most Federal excise taxes. By submittal of a properly executed response to a bid request from the Authority, the bidder is acknowledging that he is aware of his responsibilities for Federal excise taxes.

11. Tangible personal property purchased by Contractors in the performance of construction for the Authority is taxable, though the Authority is exempt for its own purchases.

12. Permits. Licenses. Taxes: In compliance with Section 218.80, F.S., all permits necessary for the prosecution of the Work shall be obtained by the Contractor. In addition, the Contractor shall comply with all rules, regulations and laws of Authority, the State of Florida, and the U.S. Government now in force or hereafter adopted.

13. The Authority reserves the right to accept item or group of items of this bid, unless the bidder qualified his bid by specific limitations.

14. The Authority reserves the right to award any item or groups of items to more than one vendor on any bid unless otherwise noted in the bid specifications.

15. Alternate bids will not be considered unless authorized by the Invitation for Bids.

16. Payment will be made by the Authority within thirty (30) days from receipt and acceptance by the Authority of delivery of the bid item or receipt of invoice for same, whichever is received later.

17. The Authority recognizes fair and open competition as a basic tenet of public procurement. Respondents doing business with the Authority are prohibited from discriminating on the basis of race, color, creed, national origin, handicap, age or sex.

18. The Authority has a Disadvantaged, Minority and Women-Owned Business Enterprises Program in place and encourages Disadvantaged, Minority and Women-Owned Business Enterprises to participate in its bid processes. All bidders are required to make all efforts reasonably necessary to ensure that Disadvantaged, Minority and Women-Owned Business Enterprises have a full and fair opportunity of compete.

19. For bidders who wish to receive copies of bids after the bid opening, the Authority reserves the right to recover all costs associated with the printing and distribution of such copies.

20. Any actual or prospective respondent to an Invitation for Bid, who is aggrieved with respect to the former, shall file a written protest with the Executive Director prior to the opening of the Bid or the due date for acceptance of Bids. All such protests must be filed with the Executive Director no later than 8:00 a.m. on the advertised date for the opening of the Bid or the acceptance date for the Bids.

21. Bid award selection criteria are as follows:

a. All questions on the Bid Form shall be answered as to price(s), time requirements, prompt payment terms (discounts), required document submissions and acknowledgment of addenda received.

b. Award shall be based upon the responses to all questions on the Bid Form.

c. Further consideration will include but not be limited to references, completeness of bid response and past performances on other Authority bids/projects.

d. Prices will be read in public exactly as written on the Bid Form at the time of the bid opening; however, should an error in calculations occur whenever unit pricing and price extensions are requested, the unit price shall prevail.

Mathematical miscalculations may be corrected by the Authority to reflect the proper answer.

22. Award of contract will be based on the best interest of the Authority and made in a manner consistent with the Authority's Purchasing Procedures. Any actual or prospective respondent who desires to formally protest the recommended contract award must file a notice of intent to protest with the Executive Director within two (2) calendar days (excluding weekends and Authority holidays) of the date that the recommended award is posted. Upon filing of said notice, the protesting party will have five (5) days to file a formal protest and will be given instructions as to the form and content requirements of the formal protest.

23. All firms are hereby placed on NOTICE that the Authority does not wish to be lobbied, either individually or collectively, about a project for which a firm has submitted a bid. Firms and their agents are not to contact members of the Authority Board of Commissioners for such purposes as meetings of introduction, luncheons, dinners, etc. During the bidding process, from bid opening to final approval, no firm or their agent shall contact any other employee of Authority with the exception of the Department Director initiating the bid process.

24. If the bidder should be of the opinion that the meaning of any part of the Bidding Document is doubtful, obscure or contains errors or omissions he should report such opinion to the Assistant Director before the bid opening date.

25. The Authority assumes no responsibility for bids received after the due date and time, or at any office or location other than that specified herein, whether due to mail delays, courier mistakes, mishandling, inclement weather or any other reason. Late bids may be returned unopened, or may or may not be considered for award.

B. **Specifications for Equipment**

1. The undersigned, as bidder, hereby declares that he has examined the specification and informed himself fully in regard to all conditions pertaining to the furnishing and delivering an ARFF Vehicle per the following specifications. The Bidder further declares that the only persons, company or parties interested in the Invitation for Bid, the award of the Bid or the Contract to be entered into as principals are named herein; that this Bid is made without connection with any other person, company or companies submitting a Bid; and it is in all respects, fair and in good faith, without collusion or fraud.

2. ARFF apparatus shall meet the criteria established in the Federal Aviation Advisory Circular 150/5220-10E and FAR Part 139.317 (b)(1). Both documents referenced are hereby incorporated into this Bid Specification. In those areas where the requirements conflict with that of the FAA, the Federal Aviation Advisory Circular 150/5220-10E shall prevail.

3. All items in the specifications are commercially available. The fact that a manufacturer chooses not to provide a required item does not make the specification proprietary in nature.

4. Option Selection Worksheets of Advisory Circular 150/5220-10E are included within this bid as Attachment #1, in order to provide subsystem component/performance selections in order for vehicle to fit the airport's identifiable operations needs.

5. Any discounts or terms must be shown on the Bid Form. Such discounts, if any, will be considered and computed in the tabulation of the bids. In no instance should terms for less than fifteen (15) days payment be offered.

6. The Bidder proposes and agrees, if the Bid is accepted, to furnish and deliver the new ARFF Vehicle in complete accordance with these specifications and price. Apparatus shall NOT be delivered under its own power; rail or truck freight is acceptable. The apparatus and its accessories, spare parts and tools shall be packaged in such a manner as to prevent pilferage and insure safe delivery.

7. The bidder shall make deliveries within three hundred sixty five (365) days of Notice of Award. All deliveries shall be made in accordance with good-commercial practice and shall be adhered to by the successful bidder; except in such cases where the delivery will be delayed due to acts of God, strikes, or other causes beyond the control of the bidder. In these cases, the bidder shall notify the Authority of the delays in advance of the delivery date so that a revised delivery schedule can be negotiated.

8. Should the bidder to whom the contract is awarded fail to deliver in the number of days as stated in its proposal, the Authority reserves the right to cancel the contract.

9. The successful bidder shall provide an intensive training program as specified in Federal Aviation Advisory Circular 150/5220-10E. The bidder shall bear all costs

associated with this training, including, but not limited to, manuals, texts, instructional materials, transportation and lodging expenses.

C. Bid Summary Form

Bid Item: One 4 X4 1500 Gallon Aircraft Rescue Firefighting (ARFF) Vehicle

Bid: _____

_____

Please state your Payment Terms and Discount if Applicable:
_____% _____ Days; Net _____ Days

Addenda received (if applicable): #1 ____ #2 ____ #3 ____

Delivery _____ days after receipt of order.

The service to be furnished by us is hereby declared and guaranteed to be in conformance with the specifications of the Authority.

The undersigned do agree that should this Bid be accepted, the execution of the contract and presenting the same to the Authority for approval will be within seven (7) days after being notified of the awarding of the Contract.

The undersigned do further agree that failure to execute and deliver said forms of the contract within seven (7) days, will result in damages to the Authority.

IN WITNESS WHEREOF, WE have hereunto subscribed our names on this ___ day of _____, 2014.

_____
Firm's **Complete Legal** Name

_____
Phone No.

_____
Fax No.

_____
E-mail

_____
Address

_____
City, State, ZIP

BY: _____
Typed and Written Signature

_____
Title

THIS SHEET MUST BE SIGNED BY BIDDER

Charlotte County Airport Authority

BIDDER'S CHECKLIST

IMPORTANT: Please read carefully, sign in the spaces indicated and return with your bid proposal.

1. The Bid has been signed and 2 copies are included.
2. The Bid prices offered have been reviewed.
3. The price extensions and totals have been checked.
4. The payment terms have been indicated.
5. Any required drawings, descriptive literature, photographs, etc. have been included.
6. Any delivery information required is included in the pricing schedule.
7. The amount of the bid bond has been checked, and the bid bond or cashiers check has been included.
8. Any addenda have been signed and included.
9. The mailing envelope has been addressed to:

   Charlotte County Airport Authority
   28000 Airport Road A-1
   Punta Gorda, Florida 33982

10. The mailing envelope must be sealed and marked with:

    Bid Title: ARFF Truck
    Opening Date: 2 p.m., 21 February 2014

11. The bid will be mailed or delivered in time to be received no later than the specified opening date and time. (Otherwise the bid may not be considered.)

ALL COURIER DELIVERED BIDS MUST HAVE THE BID TITLE ON THE OUTSIDE OF THE COURIER PACKET.

_____
Company Name

_____
Signature and Title

_____
Date

3.4. VEHICLE PROCUREMENT SPECIFICATION, CLASS 4

PROCUREMENT SPECIFICATION
Class 4
AIRCRAFT RESCUE AND FIRE FIGHTING (ARFF) VEHICLE

1. SCOPE. This Procurement Specification (PS) covers a commercially produced diesel engine driven ARFF vehicle for an Index C airport. It includes a 1500 gallon water/Aqueous Film Forming Foam (AFFF) fire suppression system:
450 lb potassium-based dry chemical only.

The ARFF vehicle is intended to carry rescue and fire fighting equipment for the purpose of rescuing aircraft passengers, preventing aircraft fire loss, and combating fires in aircraft.

2. CLASSIFICATION. The ARFF vehicle(s) covered by this PS are classified in accordance with Part 139, Certification and Operations: Land Airports Serving Certain Air Carriers, Section 315, Aircraft Rescue and Firefighting: Index Determination; Section 317, Aircraft Rescue and Firefighting: Equipment and Agents; and Federal Aviation Administration (FAA) Advisory Circular (AC) 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles, as follows:

Airport Index	Vehicle Class	Minimum Rated Capacities (gallons/liters)
Index C	4	1500 gallon (5678 liter) water/AFFF solution

3. VEHICLE CONFORMANCE/PERFORMANCE CHARACTERISTICS. The ARFF vehicle will be in accordance with the applicable requirements of National Fire Protection Association (NFPA) 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

3.1 General Administration Requirements.

3.1.1 Manuals: Technical manuals will consist of operator, service, and parts manuals. All manuals are required to be provided in hardcopy and in digital format on CDs when requested.

3.1.1.1 Technical manuals. The overall format for the manuals will be commercial. Each technical manual will have a title page. Line art will be used to the maximum extent possible for illustrations and parts lists. One complete set of engine and transmission parts, service and operator's manuals will be packed with each vehicle.

a. The contractor will provide digitized manuals in CD format when requested in addition to or in place of printed paper copies.

b. The contractor will provide two complete sets of hardcopy manuals and / or CDs when requested.

3.1.1.1.1 Operator's manual. The operator's manual will include all information required for the safe and efficient operation of the vehicle, including fire extinguishing systems, equipment, and any special attachments or auxiliary support equipment. As a minimum, the operator's manual will include the following:

a. The location and function of all controls and instruments will be illustrated and functionally described.

b. Safety information that is consistent with the safety standards established by the Occupational Safety and Health Administration (OSHA) and NFPA.

c. All operational and inspection checks and adjustments in preparation for placing the vehicle into service upon receipt from the manufacturer.

d. Tie down procedures for transport on a low-boy trailer.

e. Warranty information and the period of the warranty coverage for the complete vehicle and for any component warranty that exceeds the warranty of the complete vehicle. Addresses and telephone numbers will be provided for all warranty providers.

f. General description and necessary step-by-step instructions for the operation of the vehicle and its fire extinguishing system(s) and auxiliary equipment.

g. A description of the post-operational procedures (draining, flushing, re-servicing, et cetera).

h. Daily maintenance inspection checklists that the operator is expected to perform, including basic troubleshooting procedures.

i. Disabled vehicle towing procedures.

j. Procedures and equipment required for changing a tire.

k. Schedules (hours, miles, time periods) for required preventative maintenance and required periodic maintenance.

l. Line art drawing of the vehicle, including panoramic views (front, rear, left, and right sides) showing basic dimensions and weights (total vehicle and individual axle weight for the unloaded and fully loaded vehicle). For the purposes of this AC, "unloaded" is defined as a lack of agent, occupants and compartment load, and "loaded" is defined as including agent, occupants and compartment load.

3.1.1.1.2 Service manual. The service manual will identify all special tools and test equipment required to perform servicing, inspection, and testing. The manual will cover troubleshooting and maintenance as well as minor and major repair procedures. The text will contain performance specifications, tolerances, and fluid capacities; current, voltage, and resistance data; test procedures; and illustrations and exploded views as may be required to

permit proper maintenance by qualified vehicle mechanics. The manual will contain an alphabetical subject index as well as a table of contents. The service manual will contain at least the following, where applicable:

a. Fire fighting system schematic(s).

b. Hydraulic schematic.

c. Pneumatic schematic.

d. Electrical schematic.

e. Winterization schematic.

f. Fuel schematic.

g. Schedules for required preventative maintenance and required periodic maintenance.

h. Lubrication locations, procedures, and intervals for parts of the vehicle and equipment that require lubrication.

3.1.1.1.3 Parts identification manual. The parts manual will include illustrations or exploded views (as needed) to identify properly all parts, assemblies, subassemblies, and special equipment. All components of assemblies shown in illustrations or exploded views will be identified by reference numbers that correspond to the reference numbers in the parts lists. All purchased parts will be cross-referenced with the original equipment manufacturer's (OEM) name and part number. The parts identification manual will provide the description and quantity of each item used for each vehicle. The size, thread dimensions, torque specifications, and special characteristics will be provided for all nonstandard nuts, bolts, screws, washers, grease fittings, and similar items. The manual will contain a numerical index. The parts manual will contain a list of all of the component vendor names, addresses, and telephone numbers referenced in the parts list.

3.1.2 Painting, plating, and corrosion control.

3.1.2.1 Finish. Exterior surfaces will be prepared, primed, and painted in accordance with all of the paint manufacturer's instructions and recommendations. Vehicles will be painted and marked in accordance with AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport. The interior finish of all compartments will be based on the manufacturer’s standard production practice. This may include painting, texturing, coating or machine swirling as determined by the manufacturer. All bright metal and anodized parts, such as mirrors, horns, light bezels, tread plates, and roll-up compartment doors, will not be painted. All other surfaces capable of being painted must be in the appropriate yellow-green color.

3.1.2.2 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889, Dissimilar Metals, will not be in contact with each other. Metal plating or metal spraying of dissimilar base metals to provide electromotively compatible abutting surfaces is acceptable. The use of

dissimilar metals separated by suitable insulating material is permitted, except in systems where bridging of insulation materials by an electrically conductive fluid can occur.

3.1.2.3 Protection against deterioration. Materials that deteriorate when exposed to sunlight, weather, or operational conditions normally encountered during service will not be used or will have a means of protection against such deterioration that does not prevent compliance with performance requirements. Protective coatings that chip, crack, or scale with age or extremes of climatic conditions or when exposed to heat will not be used.

3.1.2.4 Reflective stripes. A minimum eight (8) inch horizontal band of high gloss white paint or white reflective tape (Retroreflective, ASTM-D 4956-09, *Standard Specification for Retroreflective Sheeting for Traffic Control*, TYPE III & above) must be applied around the vehicle's surface.

3.1.2.5 Lettering. The manufacturer will apply the airport's 'Name' and 'Insignia' (if available) in a contrasting color or by decal on both sides of the vehicle in long radius elliptical arches above and below the lettering center line. The size of the lettering will be a minimum of 2½-inches to a maximum of 6-inches. Reflective lettering is allowed if the material is the same as that which is used for the reflective stripe (as specified in AC 150/5210-5).

3.1.3 Vehicle identification plate. A permanently marked identification plate will be securely mounted at the driver's compartment. The identification plate will contain the following information:

a. NOMENCLATURE

b. MANUFACTURER'S MAKE AND MODEL

c. MANUFACTURER'S SERIAL NUMBER

d. VEHICLE CURB WEIGHT: kg (pounds)

e. PAYLOAD, MAXIMUM: kg (pounds)

f. GROSS VEHICLE WEIGHT (GVW): kg (pounds)

g. FUEL CAPACITY AND TYPE: gals (gallons)

h. DATE OF DELIVERY (month and year)

i. WARRANTY (months and km (miles))

j. CONTRACT NUMBER

k. PAINT COLOR AND NUMBER

A second permanently marked information data plate will be securely mounted on the interior of the driver's compartment. The plate will contain the information required by NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition), Section 1.3.5 Vehicle

Information Data Plate. A single plate that combines or contains the information required for both plates is acceptable.

3.1.4 Environmental conditions.

3.1.4.1 Vehicle operation and storage temperature conditions will vary with geographical location. Thus, the locality temperature range can go from -40° to 110°F. Refer to NFPA 414 for vehicle winterization criteria.

3.1.4.2 Temperature range. The vehicle will be capable of satisfactory storage and operation in temperatures ranging from 33° to 110°F. The vehicle will be equipped with a cab, chassis, and agent winterization system, permitting operation at 33°F. The winterization system will not detract from the performance of the vehicle or the firefighting system in ambient temperatures up to 110°F.

3.1.5 Reduction of potential foreign object damage. All loose metal parts, such as pins, will be securely attached to the vehicle with wire ropes or chains. Removable exterior access panels, if provided, will be attached with captive fasteners.

3.1.6 Vehicle Mobility.

3.1.6.1 Operating terrain. The vehicle will be capable of operating safely on paved roads, graded gravel roads, cross country terrain, and sandy soil environments. Cross country terrain consists of open fields, broken ground, and uneven terrain. An off-road, high-mobility suspension system resulting in no more than 0.5 G_{rms} acceleration at the driver's seat of the vehicle when traversing an 8-inch (20 cm) diameter half round at 35 mph (56 kph) must be provided. The suspension design by which the manufacturer meets the suspension performance requirements is at the manufacturer's discretion.

3.1.6.2 Gradeability. The fully loaded vehicle will be able to ascend any paved slope up to and including 50-percent.

3.1.6.3 Side slope stability. The fully loaded vehicle will be stable on a 30° side slope when tested in accordance with NFPA 414.

3.1.6.4 Cornering stability. The fully loaded vehicle will be stable in accordance with NFPA 414 when tested in accordance with NFPA 414.

3.2 Weights and dimensions.

3.2.1 Overall dimensions. The maximum dimensions listed below are desirable to ensure vehicles can be accommodated in existing fire stations. Likewise, the overall dimensions should be held to a minimum that is consistent with the best operational performance of the vehicle and the design concepts needed to achieve this performance and to provide maximum maneuverability in accordance with NFPA 414.

Vehicle Capacity /Dimensions	**1500 Gallon**
Length (inches/cm)	433/1100
Width (inches/cm, excluding mirrors)	124/315
Height (inches/cm)	154/391

NOTE: *For Airport Operator Validation: Consult AC 150/5210-15, Aircraft Rescue and Fire Fighting Station Building Design, Appendix A, to ensure vehicles measurements do not exceed existing airport fire station dimensions.*

VEHICLE MEASUREMENT VALIDATION

Not applicable.

ADO/FAA Approval: ⇨ _____

3.2.2 Angles of approach and departure. The fully loaded vehicle will have angles of approach and departure of not less than 30°.

3.2.3 Field of vision. The vehicle will have a field of vision in accordance with NFPA 414.

3.2.3.1 Mirrors. Combination flat and convex outside rearview mirrors will be installed on each side of the cab. The flat mirrors will be of the motorized remote control type, providing not less than 60° horizontal rotational viewing range. The flat mirrors will also have electrically heated heads. Mirror remote and heating controls will be located on the instrument panel within reach of the seated driver. To provide the driver a clear view of the area ahead of the vehicle and to eliminate potential blind spots, a rectangular mirror will be installed on the lower corner of each side of the windshield, having a minimum area of 35 square inches.
The vehicle will have a back-up (rear-view) camera with a display monitor mounted above the driver in the cab. Cameras and monitors that are designed to replace the function of the side-view mirrors are not an approved option in this specification.

3.3 Chassis and vehicle components.

3.3.1 Engine. The vehicle will have a turbocharged diesel engine that is certified to comply with the Environmental Protection Agency (EPA) and state laws for off-highway emission requirements at the time of manufacture. The engine and transmission must operate efficiently and without detrimental effect to any drive train components when lubricated with standard, commercially available lubricants according to the recommendations of the engine and transmission manufacturers.

3.3.1.1 Acceleration. The fully loaded vehicle will accelerate from 0 to 50 miles per hour (mph) on a level paved road within: 25 seconds.

3.3.1.2 Maximum speed. The fully loaded vehicle will attain a minimum top speed of 70 mph on a level, paved road.

3.3.1.3 Pump and roll on a 40-percent grade. The fully loaded vehicle will be capable of pump and roll operations on a paved, dry, 40-percent grade in accordance with NFPA 414.

3.3.1.4 Altitude. Where justified, the vehicle, including the pumping system, will be designed for operation at 2,000 feet above sea level.

JUSTIFICATION

ADO/FAA Approval: ⇨_____

3.3.2 Engine cooling system. The engine cooling system will be in accordance with NFPA 414. A label will be installed near the engine coolant reservoir reading “Engine Coolant Fill.”

3.3.3 Fuel system. The fuel system will be in accordance with NFPA 414.

3.3.3.1 Fuel priming pump. The vehicle will be equipped with an electric or pneumatic fuel pump in addition to the mechanical fuel pump. The electric/pneumatic pump will be used as a priming pump capable of re-priming the engines fuel system.

3.3.3.2 Fuel tank. The vehicle will have one or two fuel tanks with a minimum usable capacity in accordance with NFPA 414, as amended by NFPA 414. Each tank will have a fill opening of 3 inches minimum, readily accessible to personnel standing on the ground and designed to prevent fuel splash while refueling. Each tank will be located and mounted so as to provide maximum protection from damage, exhaust heat, and ground fires. If more than one tank is furnished, means will be provided to assure equalized fuel level in both tanks. An

overturn fuel valve will be provided for each tank to prevent spillage in the event of a rollover. Each fuel tank must be prominently labeled “Diesel Fuel Only”.

3.3.4 Exhaust system. The exhaust system will be in accordance with NFPA 414. The exhaust system will be constructed of high grade rust resistant materials and protected from damage resulting from travel over rough terrain. The muffler(s) will be constructed of aluminized steel or stainless steel. Exhaust system outlet(s) will be directed upward or to the rear, away from personnel accessing equipment compartments and the engine air intake, and will not be directed toward the ground.

3.3.5 Transmission. A fully automatic transmission will be provided. The transmission will be in accordance with NFPA 414.

3.3.6 Driveline. The vehicle driveline will be in accordance with NFPA 414. If the driveline is equipped with a differential locking control, a warning/caution label will be placed in view of the driver indicating the proper differential locking/un-locking procedures. The operator’s manual will also include a similar warning/caution. All moving parts requiring routine lubrication must have a means of providing for such lubrication. There must be no pressure lubrication fittings where their normal use would damage grease seals or other parts.

3.3.7 Axle capacity. Each axle will have a rated capacity, as established by the axle manufacturer, in accordance with NFPA 414.

3.3.8 Suspension. The suspension system will be in accordance with NFPA 414 and AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles.

3.3.9 Tires and wheels. Tires and wheels will be in accordance with NFPA 414. The vehicle will be equipped with single tires and wheels at all wheel positions. The vehicle will be equipped with tubeless steel belted radial tires with non-directional on/off-road type tread mounted on disc wheel assemblies. Tire and wheel assemblies will be identical at all positions. Tires and wheels will be certified by the manufacturer for not less than 25 miles of continuous operation at 60 mph at the normal operational inflation pressure. A spare tire and wheel assembly will be provided; however, the spare tire and wheel assembly are not required to be mounted on the vehicle. Tires will be new. Retreads, recaps, or re-grooved tires will not be permitted.

Tire bead locks, where justified, may be installed on all tires and rims.

JUSTIFICATION

ADO/FAA Approval: ⇨_____

3.3.10 Towing connections. The vehicle will be equipped with towing connections in accordance with NFPA 414. The vehicle will be designed for flat towing; the capability to lift and tow the vehicle is not required. The tow connections may intrude into the 30 degree approach angle.

3.3.11 Brake system. The vehicle will be equipped with a multi-channel all-wheel antilock brake system with at least one channel for each axle. The brakes will be automatic, self-adjusting and fully air-actuated. Brakes will be in accordance with CFR 49 CFR 393.40 through 393.42(b)), 393.43, and 393.43 through 393.52. The braking system, complete with all necessary components will include:

a. Air compressor having a capacity of not less than 16 standard cubic feet per minute (SCFM).

b. Air storage reservoir(s), each tank equipped with drain (bleed) valves, and with safety and check valves between the compressor and the reservoir tank.

c. Automatic moisture ejector on each air storage reservoir. Manual air tank drains are acceptable if they are labeled, are centrally located in one compartment and are accessible by an individual standing at the side of the vehicle.

d. Automatic slack adjusters on cam brakes or internal self-adjusting brakes on wedge brakes on all axles.

e. Spring set parking brakes.

All components of the braking system will be installed in such a manner as to provide adequate road clearance when traveling over uneven or rough terrain, including objects liable to strike and cause damage to the brake system components. No part of the braking system will extend below the bottom of wheel rims, to ensure, in case of a flat tire, that the weight of the vehicle will be supported by the rim and the flat tire and not be imposed on any component of the braking system. Slack adjusters and air chambers will be located above the bottom edge of the axle carrier.

3.3.11.1 Air dryer. A replaceable cartridge desiccant air dryer will be installed in the air brake system. The dryer will have the capability of removing not less than 95 percent of the moisture in the air being dried. The dryer will have a filter to screen out oil and solid contaminants. The dryer will have an automatic self-cleaning cycle and a thermostatically controlled heater to prevent icing of the purge valve.

3.3.11.2 Compressed air shoreline or vehicle-mounted auxiliary air compressor. A flush mounted, check valved, auto-eject compressed air shoreline connection will be provided to maintain brake system pressure while the vehicle is not running. The shoreline will be flush mounted (not to extend outside the body line), located on the exterior of the vehicle, either on the left side rear corner of the cab, or at the rear of the vehicle. In lieu of a compressed air shoreline connection, the vehicle may be equipped with a 110 volt shoreline connected vehicle-mounted auxiliary air compressor. In lieu of a compressed air shoreline connection, the vehicle may be equipped with an electrical shoreline connected vehicle mounted auxiliary air compressor.

3.3.12 Steering. The vehicle will be equipped with power steering. Rear-wheel steering technology is not an approved vehicle option.

3.3.12.1 Steering effort. The steering system performance will be in accordance with NFPA 414.

3.3.12.2 Turning diameter. The fully loaded vehicle will have a wall to wall turning diameter of less than three times the overall length of the vehicle in both directions in accordance with NFPA 414.

3.3.13 License plate bracket. A lighted license plate bracket will be provided at the left rear and left front of the vehicle. The location of the left front bracket will be placed so as not to interfere with the operation of fire fighting systems.

3.4 Cab. The vehicle will have a fully enclosed two door cab of materials which are corrosion resistant, such as aluminum, stainless steel, or glass reinforced polyester construction. Steps and handrails will be provided for all crew doors, and at least one grab handle will be provided for each crew member, located inside the cab for use while the vehicle is in motion. The lowermost step(s) will be no more than 22 inches above level ground when the vehicle is fully loaded. A tilt and telescoping steering column will be provided.

3.4.1 Windshield and windows. The windshield and windows will be of tinted safety glass. Each door window will be capable of being opened far enough to facilitate emergency occupant escape in the event of a vehicle accident. The vehicle windows will have an electric control system.

3.4.2 Cab interior sound level. The maximum cab interior sound level will be in accordance with NFPA 414.

3.4.3 Instruments and controls. All instruments and controls will be illuminated and designed to prevent or produce windshield glare. Gauges will be provided for oil pressure, coolant temperature, and automatic transmission temperature. In addition to the instruments and controls required by NFPA 414, the following will be provided within convenient reach of the seated driver:

a. Master warning light control switch,

b. Work light switch(es), and

c. Compartment "Door Open" warning light and intermittent alarm that sounds when a compartment door is open and the parking brakes are released or the transmission is in any position other than neutral.

3.4.4 Windshield deluge system. The vehicle will be equipped with a powered windshield deluge system. The deluge system will be supplied from the agent water tank and will have an independent pumping system. The deluge system activation switch will be located within reach of the seated driver and turret operator.

3.4.5 Forward Looking Infrared (FLIR). A forward looking infrared (FLIR) camera and in-cab monitor, meeting the requirements of NFPA 414, will be provided. In addition, the FLIR monitor described in NFPA 414 will have a minimum dimension of 10 in (25 cm) (measured diagonally) and be located in a position where it is visible to both the seated driver and turret operator.

3.4.6 Climate control system. The offeror/contractor's standard heater/defroster and air conditioning system will be provided. The climate control system will induct at least 60 cubic feet per minute of fresh air into the cab. Cab mounted components will be protected from inadvertent damage by personnel.

3.4.7 Seats. The driver seat will be adjustable fore and aft and for height. The turret operator's seat, located to the right front of the driver's seat, will be a fixed (non-suspension) type. Each seat will be provided with a Type 3 seat belt assembly (i.e., 3-point retractable restraint) in accordance with CFR 49 CFR 571.209. Seat belts must be of sufficient length to accommodate crew members in full Personal Protective Equipment (PPE).

3.4.7.1. Seat Options. Two types of seat options are allowed in the vehicle. A standard seat contains a hard/fixed back. For these seats, a remote-mounted bracket designed to store a Self–Contained Breathing Apparatus (SCBA) will be provided. The remote-mounted bracket for the driver and turret operator (at a minimum) must be placed inside the cab. The brackets for seat positions #3 and #4 may be placed outside of the cab if necessary. An SCBA seat, on the other hand, contains an opening which can accommodate someone wearing an SCBA. The chart below represents the user's stated preference for the vehicle seating configuration.

Position	Standard	SCBA-Seat	N/A
Driver		X	
Turret		X	
# 3			X
# 4			X

JUSTIFICATION

ADO/FAA Approval: ⇨_____

3.4.8 Windshield wipers and washer. The vehicle will be equipped with electrically powered windshield wipers. The wiper arms and blades will be of sufficient length to clear the windshield area described by SAE J198, Windshield Wiper Systems - Trucks. Individual wiper controls will include a minimum of two speed settings and an intermittent setting. The wiper blades will automatically return to a park position, out of the line of vision. The vehicle will be equipped with a powered windshield washer system, including an electric fluid pump, a minimum one gallon fluid container, washer nozzles mounted to the wiper arms (wet arms), and a momentary switch.

3.4.9 Warning signs. Signs that state "Occupants must be seated and wearing a seat belt when apparatus is in motion" will be provided in locations that are visible from each seated position in accordance with NFPA 414."

3.4.10 Lateral accelerometer and/or stability control system. The vehicle will be equipped with a lateral accelerometer and/or an electronic stability control system in accordance with NFPA 414.

3.4.11 Monitoring and Data Acquisition System (MADAS). The vehicle will be equipped with a MADAS as prescribed by NFPA 414.

3.5 Body, compartments, and equipment mounting.

3.5.1 Body. The vehicle will have a corrosion-resistant body.

3.5.2 Compartments. The vehicle body will have lighted compartments in accordance with NFPA 414 with a minimum of 10 cubic feet of enclosed storage space.

3.5.2.1 Compartment doors. Storage compartments will have clear anodized aluminum, counterbalanced, non-locking, roll-up or single hinged doors as determined by the manufacturer. Door latch handles on roll-up doors will be full-width bar type. Door straps will be provided to assist in closing the compartment doors when the rolled up or hinged door height exceeds six feet above the ground.

3.5.2.2 Scuffplates. Replaceable scuffplates will be provided at each compartment threshold to prevent body damage from sliding equipment in and out of the compartments. The scuffplates will be securely attached to the compartment threshold but will be easily replaceable in the event of damage.

3.5.2.3 Drip rails. Drip rails will be provided over each compartment door.

3.5.2.4 Shelves. An adjustable and removable compartment shelf will be provided for every 18 inches of each vertical storage compartment door opening. Shelving adjustments will require no more than common hand tools, and will not require disassembly of fasteners. Shelves will support a minimum of 200 pounds without permanent deformation. Each shelf will be accessible to crew members standing on the ground or using a pull out and tip-down configuration. Each shelf will have drain holes located so as to allow for drainage of any water from the stowed equipment.

3.5.2.5 Drainage mats. Each compartment floor and shelf will be covered with a removable black mat designed to allow for drainage of any water from the stowed equipment.

3.5.3 SCBA storage tubes. A single compartment or tubes for storage of four SCBA bottles will be provided. If tubes are provided, two will be installed on each side of the vehicle. The tubes will be of sufficient size to accommodate the procuring agencies SCBA cylinders.

3.5.4 Ladder, handrails, and walkways. Ladder, stepping, standing, and walking surfaces will be in accordance with NFPA 414. Handrails will be provided in accordance with NFPA 414. The lowermost step(s) or ladder rungs will be no more than 22 inches (56 cm) above level ground when the vehicle is fully loaded. The lowermost steps may extend below the angle of approach or departure or ground clearance limits if they are designed to swing clear. The tread of the bottom steps must be at least 8 inches (20 cm) in width and succeeding steps at least 16 inches (40 cm) in width. The full width of all steps must have at least 6 inches (15 cm) of unobstructed toe room or depth when measured from, and perpendicular to, the front edge of the weight-bearing surface of the step.

3.5.5 Ancillary equipment. Ancillary equipment listed in NFPA 414 A.4.2.1 (1)-(17) is not covered by this Procurement Specification in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. Ancillary equipment is funded separately by other sources.

NOTE: Equipment funding will be obtained as a separate contract under the provisions of AC 150/5210-14, Aircraft Rescue and Fire Fighting Equipment, Tools, and Clothing.

3.6 Agent system.

3.6.1 Agent (fire) pump. The vehicle will be equipped with a centrifugal pump capable of providing the performance specified herein as prescribed by NFPA 414.

3.6.1.1 Agent system piping. All piping, couplings, and valves and associated components that come into contact with the agent will be in accordance with NFPA 414.

3.6.1.2 Tank to pump connection. A check valve and shutoff valve will be provided in each tank to pump line.

3.6.1.3 Piping, couplings, and valves. All agent system piping will conform to NFPA 414 criteria.

3.6.1.4 Overheat protection. The agent system will be equipped with an overheat protection system in accordance with NFPA 414. Overheat protection is not required on vehicles utilizing a pre-mixed pressurized foam system.

3.6.1.5 Pressure relief valves. The agent system will be equipped with pressure relief valves in accordance with NFPA 414.

3.6.1.6 Drains. The agent system will be equipped with a drainage system in accordance with NFPA 414.

3.6.2 Water tank. The vehicle will have a water tank with a manufacturer certified minimum capacity of at least 1500 gallons.

3.6.2.1 Water tank construction. The water tank will be constructed of passivated stainless steel, polypropylene, or Glass Reinforced Polyester (GRP) construction. All materials used will be capable of storing water, foam concentrate, and water/AFFF solutions.

3.6.2.2 Water tank overhead fill cover and drain. The water tank will be equipped with a 20 inch fill tower. The tower will be designed to allow for video inspection of the water tank interior. The water tank will incorporate a drainage system in accordance with NFPA 414.

3.6.2.3 Water tank overflow system and venting. The water tank will incorporate a venting system to relieve pressure on the tank during fill and discharge operations at maximum flow rates. It will have an overflow system to relieve excess fluid in the event of tank overfill. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in the track of any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.2.4 Water tank top fill opening. A top fill opening of not less than 8 inches internal diameter with a readily removable ¼-inch mesh strainer will be provided. The fill opening may be incorporated as part of the manhole cover, and will be sized to accommodate a 2½-inch fill hose.

3.6.2.5 Water tank fill connections. The water tank will incorporate National Hose thread connections and will be in accordance with NFPA 414. If the vehicle is fitted with the "structural fire fighting capability option," the additional requirements listed in paragraph 3.6.8 must be incorporated.

3.6.3 Foam system. (**NOTE**: *The requirements of section 3.6.3 do not apply to pre-mixed pressurized foam systems.*)

3.6.3.1 Foam concentrate tank. The foam concentrate tank(s) will have a manufacturer certified working capacity sufficient for two tanks of water at the maximum tolerance specified in NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment for 3 to 6 percent foam concentrate (i.e., 7.0-percent).

3.6.3.1.1 Foam tank construction. The foam tank will be constructed of passivated stainless steel, polypropylene, or GRP construction. All materials used will be capable of storing foam concentrate.

3.6.3.1.2 Foam tank drain. The foam tank will incorporate a drain and drain valve. The valve will be on the left side of the vehicle and controlled by a crew member standing on the ground. The drain line will have a minimum 1½-inch I.D. The foam tank drain outlet will be located so that the contents of the tank can be drained into 5-gallon cans and 55-gallon drums.

3.6.3.1.3 Foam tank top fill trough. The foam tank will incorporate a top fill trough mounted in the top of the tank readily accessible to at least two crew members on top of the vehicle. The top fill trough will incorporate a cover, latch, and sealed so as to prevent spillage under any operating condition. The top fill trough will be designed to allow two standard 5-gallon foam concentrate containers to be emptied simultaneously. The top fill trough neck will extend sufficiently close to the bottom of the tank to reduce foaming to a minimum during the fill operation. The top fill trough will incorporate readily removable, rigidly constructed 10 mesh stainless steel, brass or polyethylene strainers. All components in and around the top fill trough will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2 Foam tank fill connections. The foam tank will incorporate a 1.5-inch National Hose thread female hose connection on both sides of the vehicle to permit filling by an external transfer hose at flow rates up to 25-gpm. The connections will be provided with chained-on long handled plugs or rocker lug plugs. The top of the connections will be no higher than 48 inches above the ground and readily accessible. The fill lines will incorporate check valves and readily removable, rigidly constructed ¼-inch mesh strainers. All components in the foam tank fill system will be constructed of materials that resist all forms of deterioration that could be caused by the foam concentrate or water.

3.6.3.2.1 Foam tank vent and overflow system. The foam tank will incorporate a vent system to relieve pressure on the tank during fill and discharge operations at maximum flow rates and an overflow system to relieve excess liquid in the event of tank overfill. Drainage from the vent and overflow system will not flow over body panels or other vehicle components and will not be in front of or behind any of the tires. Tank vent hoses will be of the non-collapsible type.

3.6.3.3 Foam transfer pump. A foam transfer pump will be provided and mounted in a compartment on the vehicle. The pump will be capable of transferring and drawing foam liquid concentrate at adjustable flow rates up to 25-gpm directly through the pump and loading

connections (see 3.6.3.2). All materials and components that come in contact with the foam will be compatible with the foam concentrate. The pump and its plumbing will have provisions for flushing with water from the water tank. A suitable length of hose with appropriate connections will be provided for filling the foam tank from an external foam storage container.

3.6.3.4 Foam flushing system. The foam concentrate system will be designed in accordance with NFPA 414 so that the system can be readily flushed with clear water.

3.6.3.5 Foam concentrate piping. All metallic surfaces of the piping and associated components that come into contact with the foam concentrate will be of brass, bronze, or passivated stainless steel. The foam concentrate piping will be in accordance with NFPA 414.

3.6.4 Foam proportioning system. The vehicle will have a foam proportioning system for Aqueous Film-Forming Foam (AFFF) (whether 3- or 6-percent foam concentrate) in accordance with NFPA 414. If a fixed orifice plate system is used, a plate will be provided for each percentage foam concentrate; the additional plate will be securely mounted in a protected location on the vehicle. A fire vehicle mechanic will be able to interchange the plates using common hand tools.

3.6.5 Primary vehicle turret. The vehicle will be equipped with a standard roof-mounted turret, high reach extendable turret, and/or high flow bumper mounted turret to serve as the primary source of agent delivery, as specified below:

3.6.5.1 Roof turret. The roof turret will be mounted near the front of the roof of the vehicle. It will have a non-air-aspirating, constant flow, variable stream nozzle with dual flow rates for foam or water rated as specified in NFPA 414. The discharge pattern will be infinitely variable from straight stream to fully dispersed. The roof turret will be power operated; power controls will be positioned for use by the driver and the crew member seated to the right of the driver. The type of nozzle or turret drain will be per the manufacturer's recommendation.

3.6.6 Bumper turret. The vehicle will be equipped with a joystick controlled, constant flow, non-air-aspirating, variable stream type:
fixed mount low volume single rate (minimum 250 GPM) bumper turret.
The bumper turret will be capable of discharging at a minimum flow rates of foam or water as specified by the user, with a pattern infinitely variable from straight stream to fully dispersed. The bumper turret will be capable of automatic oscillation, with the range of oscillation adjustable up to 90° each side of center (left and right) with vertical travel capabilities of +45°/-20° meeting section 4.20.2 in NFPA 414.

3.6.7 Preconnected handline(s). One 200 foot, 1¾-inch pre-connected woven jacket handline(s), with a 1½-inch control valve and a pistol grip nozzle, will be located on (or accessible from) left side of the vehicle. A safety system will be provided to prevent charging of the hose until the hose has been fully deployed. The handline(s) and nozzle(s) will be in accordance with NFPA 414, and will allow for a minimum of 95 gpm at 100 psi nozzle pressure. A control for charging the handline will be provided for operation by both the driver and the turret operator.

3.6.7.1 Not applicable.

3.6.8 Not applicable.

3.6.9 Primary turret discharge nozzle. The vehicle will be equipped with a complementary agent discharge mounted parallel to the AFFF solution discharge on the primary turret mounted on the front bumper.

3.7 Dry chemical agent system. The vehicle will be equipped with a 450 lb minimum capacity potassium bicarbonate dry chemical auxiliary agent system. The propellant gas cylinder will be replaceable within fifteen minutes by two crew members standing on the ground and be equipped with a cylinder replacement hoisting system. The propellant gas cylinder will be secured to withstand off-road operations. A pressure indicator will be visible to any person opening the tank fill cap. Blow-down piping will be directed beneath the vehicle. The dry chemical agent tank will include lifting rings and will have a nameplate indicating, as a minimum, the following:

a. Extinguishing agent.
b. Capacity.
c. Weight full.
d. Weight empty.
e. Operating pressure.
f. Hydrostatic test date.
g. Type of agent required for re-servicing.

3.7.1 Not applicable.

3.7.2 Dry chemical hose reel. A hose reel, equipped with at least 100 feet of dry chemical hose, will be mounted in a compartment. Handline agent and purge controls will be mounted in or adjacent to the compartment. All electrical components will be sealed against entry of water. The hose reel will have both electric and manual rewind provisions. The manual rewind handle will be bracket mounted and stored in the compartment. A quick acting control will be provided to activate the handline from the cab of the vehicle.

3.8 Not applicable.

3.9 Electrical systems and warning devices. The vehicle will have a 12-volt or 24-volt electrical and starting system in accordance with NFPA 414.

3.9.1 Alternator. An appropriate charging system, in accordance with NFPA 414, will be provided. The minimum continuous electrical load will include operation of the air conditioning system.

3.9.2 Batteries. Batteries will be of the maintenance-free type; addition of water will not be required during normal service life. The battery cover and vent system will be designed to prevent electrolyte loss during service and to keep the top of the battery free from electrolyte.

3.9.2.1 Battery compartment. The batteries will be enclosed in a weatherproof enclosure, cover, or compartment and be readily accessible.

3.9.3 Battery charger or conditioner. The vehicle will have a DC taper type battery charger or an automatic battery conditioner, or voltage monitoring system, providing a minimum 12 amp output. The charger/conditioner will be permanently mounted on the vehicle in a properly ventilated, accessible location. The charger/conditioner will be powered from the electrical shoreline receptacle (see 3.10.1). A charging indicator will be installed next to the receptacle. When a battery conditioner is provided, the conditioner will monitor the battery state of charge and, as necessary, automatically charge or maintain the batteries without gassing, depleting fluid level, overheating, or overcharging. A slave receptacle will be provided at the rear or on either side of the vehicle cab. Battery jump studs may be installed on the exterior of the battery box in lieu of a slave receptacle.

3.9.4 Electromagnetic interference. The vehicle electrical system will be in accordance with SAE J551-2 for electromagnetic interference.

3.9.5 Work lighting.

3.9.5.1 Cab interior lights. Cab interior light levels will be sufficient for reading maps or manuals. At least one red and one white cab interior dome light will be provided.

3.9.5.2 Compartment lights. White lighting sufficient to provide an average minimum illumination of 1.0 footcandle will be provided in each compartment greater than 4.0 cubic feet and having an opening greater than 144 square inches. Where a shelf is provided, this illumination will be provided both above and below the shelf. All compartments will be provided with weatherproof lights that are switched to automatically illuminate when compartment doors are opened and the vehicle master switch is in the ‘on’ position. Light switches will be of the magnetic (non-mechanical) type.

3.9.5.3 Ladder, step, walkway, and area lights. Non-glare white or amber lighting will be provided at ladders and access steps where personnel work or climb during night operations. In addition, ground lighting will be provided. Ground lights will be activated when the parking brake is set in accordance with AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles. These area lights will be controlled with three-way switches on the cab instrument panel and near the light sources. The switch located in the cab will be a

master switch and must be turned on before auxiliary switches near the light sources are operational.

3.9.5.4 Spot/Floodlights. Two spot/floodlights will be attached at the end of the primary turret or at the end of the HRET assembly. The lights will illuminate the area covered by the turret. Both lights will be controlled from switches in the cab. Halogen lights will be used.

3.9.5.5 Flood Lights. Two fixed floodlights will be provided. One light will be mounted on the left and right sides of the vehicle. 1000W Halogen lights will be used. Both lights will be controlled from switches in the cab and will be powered by the auxiliary generator.

3.9.5.6 Scene Lights. A total of six high mounted floodlights will be provided to illuminate the work areas around the vehicle. Two lights will be mounted on the front and two will be mounted on each side of the vehicle. The lights will be powered by the vehicle alternator driven system or auxiliary generator, and the lights in the front will be controlled from switches in the cab. Halogen lights will be used.

3.9.6 Audible warning devices.

3.9.6.1 Siren. The vehicle will be equipped with an electronic siren system. The amplifier unit will include volume control and selection of "Radio," "PA," "Manual," "Yelp," "Wail," and "Hi-Lo" (European) modes, and a magnetic noise canceling microphone. The amplifier, microphone, and controls will be within reach of the driver and the turret operator. Siren activating foot switches will be located in front of the driver and the turret operator. The siren speaker will be rated at 100 watts minimum and will be located in a guarded position as low and as far forward on the vehicle as practical.

3.9.6.2 Horn. Dual forward facing air horns will be installed in protected locations near the front of the vehicle. Air horn activating foot switches will be located in front of the driver and the turret operator.

3.9.7 Emergency warning lights. All emergency warning lights must meet the requirements of AC 150/5210-5. Where applicable, halogen lights will be used as the primary light type. Lighting units will be installed on the top front, sides, and rear of the vehicle to provide 360° visibility. A switch will be provided on the instrument panel to control all of the top, side, front and rear emergency warning lights. A switch will also be provided on the instrument panel to disable all lower emergency warning lights when desired. All lighting systems will meet NFPA 414 emergency lighting criteria.

3.9.7.1 Emergency warning light color. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.7.2 Headlight flashing system. A high beam, alternating/flashing, headlight system will be provided. The headlight flasher will be separately switched from the warning light panel. All emergency warning lights will meet the requirements of AC 150/5210-5.

3.9.8 Radio circuit. The vehicle will have three separate 30 amp circuits with breakers and connections provided in a space adjacent to the driver and turret operator for installation of radios and other communications equipment after the vehicle has been delivered. To facilitate the installation of the communications equipment the manufacturer will provide three antennas pre-installed on top of the cab. ***Radios are an airport responsibility and not part of this specification.***

3.9.9 Power receptacles.

3.9.9.1 Primary power receptacles. The vehicle will have two duplex 15-amp 110-volt power receptacles, one installed adjacent to the cab door on each side of the vehicle. Each duplex receptacle will include one straight blade and one twist-lock connection. These outlets will be powered by the generator.

3.9.9.2 Auxiliary power receptacles. The vehicle will have 2-12-volt auxiliary power receptacles mounted adjacent to the driver and crew member positions, preferably in the instrument panel.

3.9.9.3 Cable reel. The vehicle will be equipped with an electrical cable reel, located within a compartment. The reel will be equipped with 200 feet of 20 amp, 600 volt, 90°C insulated electrical cable. The electrical cable will be equipped with a rubber ball stop to prevent cable pull through during rewinding operations. A four-way roller guide will be provided on the cable reel to prevent chafing of cable insulation. The cable reel will have an electric rewind motor with provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the cable reel. A portable weatherproof duplex outlet box, with built-in circuit breakers and twist-lock receptacles, will be provided for on the cable end. The cable reel will be powered by the auxiliary generator.

3.9.10 Auxiliary generator. A minimum 10 kilowatt (kW) (continuous rating), 120/240-volt, 60 hertz, diesel, hydraulic, or split shaft Power Takeoff (PTO)-driven generator will be provided.

3.10 Line voltage electrical system.

3.10.1 Electrical shoreline connection. The battery charger/conditioner will be powered from a covered, polarized, insulated, labeled, recessed (flush mounted), male, 110 volt AC auto-eject receptacle. The connection will be located on the exterior of the vehicle at the rear or on either side of the cab. A weatherproof charge meter will be installed next to the receptacle. A 15 amp rated, 110-120 volt, AC straight blade (non twist-lock) connector will be provided.

3.11 Air systems.

3.11.1 Air hose reel. An air hose reel will be provided in an enclosed compartment on the vehicle. The hose reel will be equipped with 200 feet of 3/8-inch I.D. hoseline. A 3/8 inch National Pipe Taper (NPT) fitting and female style quick disconnect will be connected to the end of the hoseline. A four-way roller guide will be provided for the hose reel to prevent hose chafing and kinking. The hoseline will be equipped with a rubber ball stop to prevent hose pull through on roller guides during rewinding operations. The hose reel will have an electric rewind motor and provisions for manual rewind in the event of motor failure; the manual rewind handle will be securely stored near the hose reel. A pressure protected air supply from the chassis air system will be connected to the hose reel. The air supply lines will be routed with minimum bends and located or guarded from damage from the carried equipment.

3.12 Quality of Workmanship. The vehicle, including all parts and accessories, will be fabricated in a thoroughly workmanlike manner. Particular attention will be given to freedom from blemishes, burrs, defects, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of welding, brazing, soldering, riveting, and painting; alignment of parts; tightness of fasteners; et cetera. The vehicle will be thoroughly cleaned of all foreign matter.

4. REGULATORY REQUIREMENTS.

4.1 Recoverable Materials. The contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with Title 48: Federal Acquisition Regulations System, Part 2823—Environment, Conservation, Occupational Safety, and Drug-free Workplace, Subpart 2823.4 Use of Recovered Material, 403 Policy and 404 Procedures.

4.2 Green Procurement Program. Green Procurement Program (GPP) is a mandatory federal acquisition program that focuses on the purchase and use of environmentally preferable products and services. GPP requirements apply to all acquisitions using appropriated funds, including services and new requirements. FAR 23.404(b) applies and states the GPP requires 100% of EPA designated product purchase that are included in the Comprehensive Procurement Guidelines list that contains recovered materials, unless the item cannot be acquired:

a. competitively within a reasonable timeframe;

b. meet appropriate performance standards, or

c. at a reasonable price.

The prime contractor is responsible for ensuring that all subcontractors comply with this requirement. Information on the GPP can be found at:
http://www.dot.gov/ost/m60/DOT_policy_letters/apl8_04.pdf or FAR 23.404(b):
http://www.acquisition.gov/far/current/html/Subpart%2023_4.html.

5. PRODUCT CONFORMANCE PROVISIONS.

5.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Performance inspection (see 5.2).

b. Conformance inspection (see 5.3).

5.2 Performance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, schedule, and facilities.

5.3 Conformance inspection. The vehicle will be subjected to the examinations and tests described in 5.6.3.1 through 5.6.3.5 (if applicable). The contractor will provide or arrange for all test equipment, personnel, and facilities.

5.4 Product conformance. The products provided will meet the performance characteristics of this PS, conform to the producer's own drawings, specifications, standards, and quality assurance practices, and be the same product offered for sale in the commercial marketplace. The purchaser reserves the right to require proof of such conformance.

5.5 Technical proposal. The offeror/contractor will provide an itemized technical proposal that describes how the proposed model complies with each characteristic of this PS; a paragraph by paragraph response to the characteristics section of this PS will be provided. The offeror/contractor will provide two copies of their commercial descriptive catalogs with their offer as supporting reference to the itemized technical proposal. The offeror/contractor will identify all modifications made to their commercial model in order to comply with the requirements herein. The vehicle furnished will comply with the "commercial item" definition of FAR 2.101 as of the date of award. The purchaser reserves the right to require the offeror/contractor to prove that their product complies with the referenced commerciality requirements and each conformance/performance characteristics of this PS.

5.6 Inspection requirements.

5.6.1 General inspection requirements. Apparatus used in conjunction with the inspections specified herein will be laboratory precision type, calibrated at proper intervals to ensure laboratory accuracy.

5.6.2 Test rejection criteria. Throughout all tests specified herein, the vehicle will be closely observed for the following conditions, which will be cause for rejection:

a. Failure to conform to design or performance requirements specified herein or in the contractor's technical proposal.

b. Any spillage or leakage of any liquid, including fuel, coolant, lubricant, or hydraulic fluid, under any condition, except as allowed herein.

c. Structural failure of any component, including permanent deformation, or evidence of impending failure.

d. Evidence of excessive wear.

e. Interference between the vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.

f. Misalignment of components.

g. Evidence of undesirable roadability characteristics, including instability in handling during cornering, braking, and while traversing all required terrain.

h. Conditions that present a safety hazard to personnel during operation, servicing, or maintenance.

i. Overheating of the engine, transmission, or any other vehicle component.

j. Evidence of corrosion.

k. Failure of the fire fighting system and sub-systems.

5.6.3 Detailed inspection requirements.

5.6.3.1 Examination of product. All component manufacturers' certifications, as well as the prototype and production/operational vehicle testing outlined in Table 1, will be examined to verify compliance with the requirements herein. Attention will be given to materials, workmanship, dimensions, surface finishes, protective coatings and sealants and their application, welding, fastening, and markings. Proper operation of vehicle functions will be verified as defined by NFPA 414, Acceptance Criteria chapter. A copy of the vehicle manufacturer's certifications will be provided with each vehicle in accordance with NFPA 414. The airport may accept a manufacturer or third party certification for any/all prototype and production/operational vehicle testing performed prior to delivery which proves that the vehicle meets the performance parameters of NFPA 414.

Table 1. Vehicle Test Data

NFPA 414 paragraph	***Test***
Production Vehicle Operational Tests (NFPA 414 - Section 6.4)	
(6.4.1)	Vehicle Testing, Side Slope
(6.4.2)	Weight / Weight Distribution
(6.4.3)	Acceleration. **NOTE:** *With the modification that the instrumentation must be a GPS-based electronic data collection system.*
(6.4.4)	Top Speed
(6.4.5)	Brake Operational Test
(6.4.6)	Air System / Air Compressor Test
(6.4.7)	Agent Discharge Pumping Test
(6.4.8)	Dual Pumping System Test (As Applicable)
(6.4.9)	Pump and Maneuver Test
(6.4.10)	Hydrostatic Pressure Test
(6.4.11)	Foam Concentration Test
(6.4.12)	Primary Turret Flow Rate Test
(6.4.13)	Piercing/Penetration Nozzle Testing (As Applicable)
Prototype Vehicle Tests (NFPA 414 – Section 6.3)	
(6.3.1)	Rated Water and Foam Tank Capacity Test
(6.3.2)	Cornering Stability. **NOTE:** *With the modification that the evasive maneuver / double-lane change test must be conducted at 35 mph (56 kph).*

NFPA 414 paragraph	*Test*
(6.3.3)	Vehicle Dimensions
(6.3.4)	Driver Vision Measurement
(6.3.5)	Pump and Roll on a 40 Percent Grade
(6.3.6)	Electrical Charging System
(6.3.7)	Radio Suppression
(6.3.8)	Gradability Test
(6.3.9)	Body and Chassis Flexibility Test
(6.3.10)	Service/Emergency Brake Test
(6.3.11)	Service/Emergency Brake Grade Holding Test
(6.3.12)	Steering Control Test
(6.3.13)	Vehicle Clearance Circle Test
(6.3.14)	Agent Pump(s)/Tank Vent Discharge Test
(6.3.15)	Water Tank Fill and Overflow Test
(6.3.16)	Flushing System Test
(6.3.17)	Primary Turret Flow Rate Test
(6.3.18)	Primary Turret Pattern Test
(6.3.19)	Primary Turret Control Force Measurement
(6.3.20)	Primary Turret Articulation Test
(6.3.21)	Handline Nozzle Flow Rate Test
(6.3.22)	Handline Nozzle Pattern Test
(6.3.23)	Ground Sweep/Bumper Turret Flow Rate Test
(6.3.24)	Ground Sweep/Bumper Turret Pattern Control Test
(6.3.25)	Undertruck Nozzle Test
(6.3.26)	Foam Concentration/Foam Quality Test
(6.3.27)	Warning Siren Test
(6.3.28)	Propellant Gas
(6.3.29)	Pressure Regulation
(6.3.30)	AFFF Premix Piping and Valves
(6.3.31)	Pressurized Agent Purging and Venting
(6.3.32)	Complementary Agent Handline Flow Rate and Range
(6.3.33)	Dry Chemical Turret Flow Rate and Range
(6.3.34)	Cab Interior Noise Test

6. PACKAGING.

6.1 Preservation, packing, and marking will be as specified in the Procurement Specification, contract or delivery order.

6.2 The vehicle must be delivered with full operational quantities of lubricants, brake and hydraulic fluids, and cooling system fluid all of which must be suitable for use in the temperature range expected at the airport.

6.3 The vehicle must be delivered with one complete load of firefighting agents and propellants. One complete load is defined as all of the agents and propellants necessary for the

vehicle to be fully operational. One load would include, at a minimum: one fill of a foam tank; one fill of a dry chemical tank (if applicable); one fill of a halogenated tank (if applicable); one spare nitrogen cylinder for a dry chemical system (if applicable); and one spare argon cylinder for a halogenated system (if applicable). Agents and propellants for required testing or training are not included. For the initial training period, water should be used in place of other extinguishing agents. The manufacturer may pre-ship agents and propellants to a receiving airport to reduce overall procurement costs.

6.4. The vehicle manufacturer must provide initial adjustments to the vehicle for operational readiness and mount any ancillary appliances purchased through the vehicle manufacturer as part of the vehicle.

7. TRAINING.

7.1 Upon delivery of the vehicle to the airport, the manufacturer must, at no additional cost, provide the services of a qualified technician for five consecutive days (or up to 8 days for an high reach extendable turret) for training. This is considered sufficient time for the purchaser to adjust shift work schedules to get maximum employee attendance to training sessions at some point during the training period. During this time sufficient repetitive learning opportunities must be provided by the manufacturer to allow various shifts to complete the training requirements.

7.2 The technician must provide thorough instruction in the use, operation, maintenance and testing of the vehicle. This setup must include operator training for the primary operators, which will give them sufficient knowledge to train other personnel in the functional use of all fire fighting and vehicle operating systems. Prior to leaving the vehicle, the technician should review the maintenance instructions with the purchaser's personnel to acquaint them with maintenance procedures as well as how to obtain support service for the vehicle.

7.3 Training must include written operating instructions, electronic training aids (videos/power point), or other graphics that depict the step-by-step operation of the vehicle. Written instructions must include materials that can be used to train subsequent new operators.

8. REFERENCED DOCUMENTS.

8.1 Source of documents.

8.1.1 The CFR may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington DC 20402.

Title 14, Code of Federal Regulations (CFR), Part 139, Certification of Airports (14 CFR Part 139)

Section 139.315 Aircraft Rescue and Firefighting: Index Determination.

Section 139.317 Aircraft Rescue and Firefighting: Equipment and Agents.

Section 139.319 Aircraft Rescue and Firefighting: Operational Requirements.

Title 49; Code of Federal Regulations (CFR), Part 393: Parts and Accessories Necessary for Safe Operation: Subpart C—Brakes.

Title 49; Code of Federal Regulations (CFR), Part 571, Motor Carrier Vehicle Safety Standards, Part 209, Standard No. 209; Seat Belt Assemblies

8.1.2 SAE documents may be obtained from SAE, Inc., 400 Commonwealth Drive, Warrendale PA 15096.

8.1.3 National Fire Protection Association (NFPA): NFPA documents may be obtained from NFPA, Batterymarch Park, Quincy MA 02269-9101.

NFPA 412, Standard for Evaluating Aircraft Rescue and Fire-Fighting Foam Equipment (2009 Edition)

NFPA 414, Standard for Aircraft Rescue and Fire Fighting Vehicles (2007 Edition)

NFPA 1901, Standard for Automotive Fire Apparatus (2009 Edition)

8.1.4 Federal Aviation Administration (FAA): FAA ACs may be obtained from the FAA website: http://www.faa.gov/regulations_policies/advisory_circulars/

AC 150/5220-10, Guide Specification for Aircraft Rescue and Fire Fighting (ARFF) Vehicles

AC 150/5210-5, Painting, Marking, and Lighting of Vehicles Used on an Airport

FAA Orders, Specifications, and Drawings may be obtained from: Federal Aviation Administration, ATO-W CM-NAS Documentation, Control Center, 800 Independence Avenue, SW, Washington, DC 20591. Telephone: (202) 548-5256, FAX: (202) 548-5501 and website: http://www.faa.gov/about/office_org/headquarters_offices/ato/service_units/techops/atc_facilities/cm/cm_documentation/

☑ **Print Class 4 Specification**

SAMPLE CONTRACT

PART AA (CONTRACT FORMS)

CHARLOTTE COUNTY AIRPORT AUTHORITY

THIS AGREEMENT made and executed into this _____ day of _____, by and between **CHARLOTTE COUNTY AIRPORT AUTHORITY** (Party of the First Part, hereinafter called the OWNER) and _____ (Party of the Second part, hereinafter called the Contractor).

WITNESSETH: that the said Contractor has agreed and by these presents does agree with the said Owner, for the consideration herein mentioned in his proposal and under the penalty expressed in Bonds, hereto attached, to furnish all equipment, tools, material, skill and labor of every description necessary to carry out and complete in good firm, substantial, and workmanlike manner, the work specified in strict conformity with the specifications hereinafter set forth, which specifications together with the foregoing Proposal made by the Contractor, General Biding Requirements, General Specifications, AC 150/5220-10E Procurement Specification Class 4 Aircraft Rescue and Fire Fighting (ARFF) Vehicle and this Agreement constitute the contract. The work covered by this Agreement includes all work described in the specifications and listed in the attached Proposal, at the Punta Gorda Airport to-wit:

Index B
Aircraft Rescue Firefighting (ARFF) Vehicle

The Contractor shall commence the work with adequate force and equipment on a date to be specified in a written order of the Owner and shall complete the work within 30 calendar days, from and including the date stipulated in the "Notice to Proceed".

The Contractor shall fully guarantee his workmanship and materials furnished for a period of one year following the date of final acceptance of the work. The performance and payment bonds shall remain in full force for this one year period.

The Owner shall pay and the Contractor shall receive the price stipulated in the Contractor's Proposal hereto attached as full compensation for everything furnished and done by the Contractor (Total) _____ in an acceptable manner, which sum shall be paid in the manner and terms specified in the Contract Documents but, before issuance of certificates of payment if the Contractor shall not have submitted evidence satisfactory to the Owner that all payrolls, materials, bills, and other indebtedness connected with the work have been paid, the Owner may withhold, in addition to the retained percentages such amount or amounts as may be necessary to pay just claims for labor and services rendered and materials in and about the work, and such amount or amounts withheld or retained may be applied by the Owner to the payment of such just claim.

It is further mutually agreed between the parties hereto that if, at any time after the execution of this agreement and the surety bond hereto attached for its faithful performance, the first party shall deem the surety or sureties upon such bonds to be unsatisfactory, or if, for any reason, such bonds cease to be adequate to cover the performance of the work, the second party shall at its